

AK-VPRG49

Android master monitor 9.0 for video door entry system
TFT display of 7" | Third-party applications
Crystal Clear two-way audio
TCP/IP, PoE, WiFi, Bluetooth, SIP Standard
Cloud-based maintenance
Connection of monitors and boards through the Cloud



Akuvox
Android TFT master monitor 9.0 for 7" video door entry
Integrated camera of 2Mpx
Built-in microphone and speaker
Two-way audio with Crystal Clear technology with noise reduction and echo cancellation
1 entry RJ9 and 2 entries RJ45
1 HDMI output, 1 jack output 3.5mm and 1 USB-C output
Image capture and recording
Multiple screen extensions
TCP/IP, WiFi and Bluetooth
1 PoE port IEEE802.3af
Easy-to-integrate SIP standard
Surface mounting
Complete configuration via Web browser
Push notifications and calls between devices through the SmartPlus App
4 free users included in the App
Call and user directory
Complete call management system
Firmware upgrades via cloud with installer control
Camera viewing via RTSP
Connection between boards and monitors via cloud in different networks
Installation of third-party applications without the need for Google Services
Remote configuration access for installation

Specifications

Brand	Akuvox
Model	VPRG49
Operating system	Android 9.0
Hardware	RAM: 2GB ROM: 8GB
Camera	2 MP CMOS
LCD	7" TFT 1024x600
Operation mode	Capacitive touch panel
Inputs	1 x RJ9, 2 x RJ45
Outputs	1 x HDMI, 1 x 3.5 mm jack, 1x USB-C
Audio	Two-way audio with noise-reduced microphone and speaker with Crystal Clear Audio technology
Audio Format	SIP v1 (RFC2543), SIP v2 (RFC3261), G.711a, G.711?, G.729, G.722 DTMF (RFC2833), SIP Info
Remote access	SmartPlus cell phone application or configuration via WEB browser Remote access by Cloud: Included
Mode of operation	Local network and/or via cloud in different networks
Firmware updates	Remote with cloud via installer account or via web browser locally
Network interface	Ethernet 10/100/1000 BaseT / RTSP / WiFi 802.11b/g/n
Power	DC 12 V / 1 A max. / Standard PoE (IEEE802.3af)
Temp. operation	-0° C ~ +40° C
Dimensions	250 (W) x 210 (H) x 98 (D) mm
Weight	1.72 kg